



NOTES:

1. FOR USE WITH RG-223, 55A, 142 & 142A/U CABLE.
2. FOR CABLE TRIMMING USE KTJ-57 & KTD-25.
3. FOR FORMING USE CRIMP DIE SIZE 01.
4. FOR CABLING INSTRUCTIONS SEE CP-401.

UNLESS OTHERWISE SPECIFIED:

- | | |
|--|---|
| <ol style="list-style-type: none"> 1. TOLERANCES:
FRACTIONS ± .010 DECIMALS ± .004 ANGLES ± 0° 30' T. I. R. CONCENTRICITY OF ANY 2 DIAMETERS MAY NOT EXCEED THE SUM OF THEIR TOLERANCES. | <ol style="list-style-type: none"> 2. REMOVE ALL BURRS, BREAK SHARP EDGES .003 MAX. 3. NO FILLETS PERMITTED. 4. SURFACE ROUGHNESS 63 MICROINCHES RMS MAX. 5. ALL DIMENSIONS PRIOR TO PLATING. |
|--|---|

S-D

KA-59-72

REVISIONS

ISSUE	CHANGES
1	CN 4587 JP 12 NOV 66
2	CN 5917 A JM 27 APR 68
3	CN 6369 A 23 AUG 68 AVE
4	CN 6645 A V.S. 3 OCT 68
5	CN 6776 A 18 NOV 68 A.M.E.
6	CN 7618 A R.H.H. 5 JUN 69
7	CN 9110 A C.C. 17 DEC 70
8	CN 11411 C CC 29 SEP 72
9	CN 12675 A JL 27 AUG 73
10	CN 13896 A CA 30 JUL 74
11	CN 17482 C NM 17 AUG 77
12	CN 17911 E NM 26 JAN 78
13	CN 19899 A FH 30 NOV 79

S-D

ITEM	REQD	DESCRIPTION	DWG NO
12	1	K-GRIP	
11	1	K-GRIP SLEEVE	S-89-05-2-MUT
10	1	TIN CRIMP CONTACT M	1-5523-M09
9	1	INSULATOR	
8	1	SOLDER PREFORM	
7	1	BODY ASSEMBLY	
6	1	BNC ANGLE CONTACT M/F	
5	1	INSULATOR	
4	1	C-RING	
3	1	GASKET	
2	1	CONTACT	
1	1	COUPLING NUT	

REF:	
FINISH	
SPEC. KER	10004
MATL	
SPEC.	TNC ANGLE PLUG
DRAWN CARE	DATE 11 DEC 65
APPR. P.E.T.	DATE 14 DEC 65
KINGS ELECTRONICS 40 MARLBOROUGH ROAD TUCKAHOE, N. Y.	
KA-59-72	

S-D